

PLYCO

CORPORATION
PO BOX Q • ELKHART LAKE, WI 53020

EQUUS DUTCH DOOR SYSTEMS

Delivered Pre-Assembled or KD

Designed with Horse Safety in Mind

Extended Jamb Available

*Heavy Duty Hinges are Extra Strong
and Bolt into the Door Panel*

*Door Panel Perimeters are Cut and
Formed from a Single Piece of 16
Gauge Steel*

**EQUUS
DUTCH DOOR SYSTEMS**



EQUUS

Dutch Doors

- Pre-Assembled Door Panels with Matching Crossbucks Assembled over Matching or Contrasting Steel Sheet
- Door Panel Perimeters are Cut and Formed from a Single Piece of 16 gauge steel
- Paint System is Quality Powder Coat Urethane over a Six Stage Pre-Wash
- Heavy Duty Hinges are Extra Strong and Bolt into the Door Panel
- For Professional Installations, a 16 gauge Pre-Punched Steel Jamb and Header System is Available

Crossbucks

- Formed with the same 16 gauge steel, then powder coat painted to match the door frame and assembled into the Dutch Door. Matching screws secure each corner and the center of the crossbuck providing a decorative finish and adding strength.

Barrel Bolt

- On the inside of the door connects the two door halves together to operate as a single door.

Standard Jamb





Dutch Door Hinge

■ Designed to be extra strong and horse safe. The large hinge half that attaches to the building has rounded corners that will not hurt a horse rubbing in passing. All hinges are "E" coated for corrosion resistance, then powder coat painted to match the door. The door hinge half is mostly concealed inside and bolts directly to the door panel. Two slotted holes in the jamb hinge half allow adjustment when the door is installed without the EJS-4700 steel jamb kit and two round holes assure sag-free final installation with or without the steel jamb.



Extended Jamb

■ Includes hinge side, strike side, and header. All pieces are formed using 16 gauge steel then powder coat painted with the same colors available for the Dutch Door components. All pieces are pre-punched with mounting holes and the hinge jamb piece is pre-punched for hinge holes to mate with the AP-4700 Dutch Door. The jamb kit provides a strong, finished appearance and helps eliminate door sag.



Dutch Door Catch Kit

■ Prevents horse injury while adding extra security. Designed & engineered for most types of swing door systems. Double sided easy operation. Heavy duty Stainless Steel and easy installation.



Bale Door

■ Allows for easy access to hay storage. Look to match AP-4700 dutch door.

PLYCO CORPORATION
USA
800/558-5895
FAX: 800/257-5926
INTERNATIONAL
920/876-3611
FAX: 920/876-3527
www.plyco.com

EQUUS Dutch Door Systems

MODEL U-4700, UNASSEMBLED DUTCH DOOR

Unassembled 16 gauge steel crossbuck and four-piece perimeter frame components are powder coat painted after six stage wash. Available in bone, chocolate, or charcoal. Shipped with galvanized hardware package that includes galvanized strap hinges, doors, barn latch, barrel bolt, catch kit, and assembly hardware.

An economical system that can be assembled in the field using your choice of 3/4" cores with or without steel skins. Kit comes cartoned.

MODEL EJS-4700, DUTCH DOOR JAMB KIT (OPTIONAL)

The three-piece steel jamb system is powder coat painted with the same high quality urethane as the door system and is pre-punched for quick, accurate, sag-free installation of the door. Not factory punched to match kit door strap hinges. **Extended Jamb Kit is also available.**

MODEL AP-4350, BALE DOOR

Allows for easy access to hay storage. Look to match AP-4700 dutch door. Same assembly and construction as AP-4700 dutch door above, including same color options. Includes four piece 16 gauge steel jamb kit and all hardware. RO: 49-1/2" x 43-15/16".

MODEL AP-4700, PRE-ASSEMBLED DUTCH DOOR

16 gauge bone, bronze, chocolate, or charcoal steel one-piece perimeter door panel frame is assembled over your choice of available colors (see chart) 29 gauge flat steel sheets attached to both sides of 3/4" exterior grade plywood.

Two heavy steel hinges per door panel are powder coat painted to match the door and bolted into the panel with only the hinge knuckle showing, providing a more finished appearance than the old strap style hinge. All hinges are "E" coated for corrosion resistance, then powder coat painted to match the door. The large size of this hinge allows the door panel to open away from building skin or trim. Nylon spacers provide smooth, quiet operation.

Hardware kit includes Black Barn Latch, Catch Kit, Assembly Hardware, and Galvanized Barrel Bolt. The Catch Kit is designed to be horse safe and is self-storing with the door closed.

Door panels and hardware are individually packaged.



DUTCH DOOR COLORS

Seventeen Powder Coat Colors available as well as additional painted colors to match most roll-formers' colors. Specify roll-former when purchasing.

Because of its ongoing commitment to product improvement, Plyco Corporation reserves the right to change, without notice, product specifications, availability, prices and conditions of sale.

PLYCO
CORPORATION
PO BOX Q • ELKHART LAKE, WI 53020

www.plyco.com 800/558-5895 FAX: 800/257-5926
INTERNATIONAL 920/876-3611 FAX: 920/876-3527

**WINDOWS • WALK DOORS • WALL VENTS • RIDGE VENTS
SLIDING DOOR TRACK • SLIDE DOOR RAILS • PLY-FOIL INSULATION
HORSE STALLS • FASTENERS & CLOSURES • SPECIALTY PRODUCTS**